

108Mbps Standard 11g PCMCIA Wireless LAN Adapter



The WL-3560 is an IEEE 802.11g Wireless PCMCIA card that can operate in either Ad-Hoc mode (Point to Point/Point to Multipoint without an Access Point) or Infrastructure mode (Point to Point/Point to Multipoint with an Access Point). IEEE 802.11g uses 2.4GHz frequency band, the same as IEEE 802.11b; but it provides almost 5 times throughput rate than 802.11b. With the latest innovative Super G technology integrated, the maximum data rate of WL-3560 is 108Mbps, which doubles the speed of standard 802.11g. WL-3560 is also backward compatible and interoperable with IEEE 802.11b compliant wireless devices. This dual-standard support allows for greater flexibility of deployment and use.

The WL-3560 supports both 64/128-Bit WEP (Wired Equivalent Privacy) and Wi-Fi Protected Access (WPA) for securing wireless network connections. The driver and utility supports most popular operating systems: Windows 98SE/ME/2000/XP/Server 2003. With advanced features and high performance capability, the WL-3560 is an excellent choice for constructing a wide range of wireless solutions.

KEY FEATURE

- Fully compliant with wireless LAN IEEE 802.11g and 802.11b standards
- Wireless connection without the difficulty and cost of cabling
- Dual-standard capability: 802.11g and 802.11b compliant
- Super G mode provides up to 108Mbps data rate
- Based on 2.4GHz Direct Sequence Spread Spectrum (DSSS) Technology
- Supports 64/128-Bit WEP (Wired Equivalent Privacy) and Wi-Fi Protected Access (WPA)
- Supports Ad-Hoc (Peer to Peer) communication and Infrastructure mode with an Access Point
- Seamless integration with IEEE 802.3 LAN through any IEEE 802.11b or 802.11g compliant Access Point
- Supports most popular operating systems including Windows 98/Me/2000/XP/Server 2003
- Low Interference and High Susceptibility Guarantee Reliable Performance
- Supports Power Save mode
- Plug-and-Play installation
- Supports eXtended Range mode

SPECIFICATION

Product	54/108Mbps Standard 11g PCMCIA Wireless LAN Adapter
Model	WL-3560
Attachment Interface	PC CardBus 32-bit compliant
LED Indicators	Two Link/Act
Operating Frequency/Channel	2.412~2.462GHz (FCC, Canada)/11 Channels 2.412~2.4835GHz (TELEC, Japan)/14 Channels 2.412~2.472GHz (ETSI, Europe)/13 Channels
RF Modulation	Direct Sequence Spread Spectrum (DSSS) Technology (OFDM, CCK, QPSK, BPSK)
RF Output Power	16-18dBm (typical)
Sensitivity	802.11g: -72dBm @ PER<8%, 54 Mbps 802.11b: -82dBm @ PER<8%, 11 Mbps
Data Rate	Super G: Up to 108Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6Mbps with auto-rate fall back 802.11b: 11, 5.5, 2, 1Mbps with auto-rate fall back
Media Access Protocol	CSMA/CA + ACK
Antenna	Built-in patch antenna
Working Mode	Ad-Hoc, Infrastructure
Dimension (L x W x H)	119 x 54 x 12 mm
Humidity	0~95%, non-condensing (Operating and storage)
Temperature	0~55 Degree C (Operating), -10~70 Degree C (Storage)
Compatibility	Windows 98SE/ME/2000/XP/Server 2003
Management	Utility or Windows XP built-in management interface
Electromagnetic Compatibility	FCC Part 15 class B, CE Mark, ETS 300 328

APPLICATIONS

WL-3560 offers a fast, reliable, cost-effective solution for wireless client access to the network in

- **Remote access to corporate network information**
E-mail, file transfer and terminal emulation.
- **Difficult-to-wire environments**
Historical or old buildings, asbestos installations, and open areas where wiring is difficult to employ.
- **Frequently changing environments**
Retailers, manufacturers and banks who frequently rearrange the workplace and change locations.
- **Temporary LANs for special projects or peak time**
Trade shows, Sports events, exhibitions and construction sites need temporary setup for a short time period. Retailers, airline and shipping companies need additional workstations for a peak period. Auditors requiring workgroups at customer sites.
- **SOHO (Small Office and Home Office) users**
SOHO users requiring quick and easy installation of a small computer network.
- **High security connection**
Wireless network security installs quickly and provides the flexibility to reconfigure easily.

ORDERING INFORMATION

WL-3560	108Mbps Standard 11g PCMCIA Wireless LAN Adapter
---------	--